



Unit #:
XX-XXXX

DEALER: XYZ Dealer
CUSTOMER: XYZ Emergency Ambulance
 Street or P.O. Box _____
 City, State, Zip _____
 Contact Contact: _____
 Sales Associate: _____
 Sales Engineer: _____

VIN#: To be assigned by MEDIX

Chassis Model Yr		2021
MEDIX Model		Type III 166
CHASSIS		Chevy/GMC 4500 Cutaway, 6.6L DI Gasoline, 159" WB 14,200 GVWR
BODY		166"L x 94"W x 72" Interior Headroom
QTY	STD/OPT	Description
1	15-6000-CD	Chassis & Conversion
	01-	Flooring & Interior Colors
1	STD	Cabinets: Laminated Wood- (Specify Color) Color:
1	STD	Upholstery: (Specify Color) Color: Brand: EVS
1	STD	Flooring: Lonseal - Lonfloor Moonstone #507
	02-	Body & Chassis
1	STD	This chassis is equipped with a Gasoline Exhaust System to meet the EPA standards for Gasoline exhaust emissions
1	STD	Anti-Theft Device: IdleLock Ignition Security System, PN: A-IDLE611 for G-3500/4500 Series Chassis Only. Locate activation button to the right side of the steering wheel.
1	STD	All Exterior compartments coated with light gray colored rubberized urethan material.
1	STD	Walk-Thru w/Sliding Door. Slides behind driver's seat
1	STD	Fender Flares: Black rubber
1	STD	Compartment Lights: Optronics ILL36CB LED Compartment lights- ALL Models
		Locate: (1) Ceiling of Compt #1; (2) in Compt #2- (1) URH, (1) LLH; (1) in ceiling of Compartment #3; (2) in Compt #4/5; (1) in Compt #6.
1	STD	Compartment #1 SS Forward: <u>Smooth Aluminum</u> body, <u>ADP interior door panel</u> , O2 "M" cylinder storage for STEEL tank, Door w/gas strut hold-open.
1	STD	Compartment #2 SS Center: <u>Smooth Aluminum</u> body, <u>ADP interior door panel</u> , Open Storage, Double Doors w/gas strut hold-opens and Seat Belt Strap.

1	STD	Compartment #3 SS Rear: 3/4 Height, <u>Smooth Aluminum</u> body, <u>ADP interior door panel</u> , Inside/Outside access with dual 1/2" Acrylic hinged doors w/non-locking Eberhard two point pinch latches. (1)-adjustable shelf. Door w/gas strut hold-open.
2	STD	Rear Entry Doors: Single piece laminated smooth aluminum door liner w/stainless steel center panel for black paddle handles; ADP kick panels.
1	STD	Compartment #4/5 CS Forward: NO body <u>above floor</u> , <u>ADP interior door panel</u> , ALS Cabinet w/ Inside/Outside access, Full-height, single Door w/gas strut hold-open. Bottom section smooth aluminum body with single battery, roll-out tray and sealed, removable, latching door.
1	STD	Curbside Entry Door: Single piece, laminated smooth aluminum door liner w/stainless steel center panel for black paddle handles; ADP kick panels. Gas strut door hold-open. Smooth aluminum stepwell w/Dri-Dek insert.
1	STD	Compartment #6 CS Rear: ADP body, Vertical backboard storage w/2 belts. Door w/gas strut hold-open.
1	STD	All Entry Door paddle handle and rotary latching components will include emergency door releases located top and bottom of each door and shall meet the FMVSS 206 30G Test Requirement
1	STD	Rear Bumper: ADP corner pods w/Dock bumper pads, Center grip-strut flip-up step, powder coated steel frame
2	STD	IV Hangers: (2) Cast black rubber fold-down over knee area of Cot and Squad Bench
2	STD	Mirrors, Velvac, 2020XG for G-series cutaway with 8D8 option, Heated/Remote Deluxe head w/bottom convex, no turns, Black, Kit# 718416
1	STD	Wheel Covers: Stainless steel covers w/Valve Extenders
4	STD	Stone Guards, lower body corners, ADP
1	STD	Kick Plate, Rear: ADP, below rear doors across to corner posts
1	STD	Rub Rails, C-Channel, tapered ends, Lower Body off-set mount with neoprene spacers.
1	STD	Fuel Fill Housing: Cast aluminum; Cast aluminum fuel fill housing
1	STD	Insulation: Pink, double sided radiant barrier/acoustic material, installed on curbside and streetside rear wheel wells.
1	STD	Insulation: Spray in place foam, FR 2-Part Spray Foam, CP-1000 Kit 200, applied to curbside entry step well and both rear wheel wells
1	STD	Undercoating: Per OEM Guidelines
	03-	Brake, Turn & Back-Up Lights
1	STD	Lights: DOT, Brake/Tail, Turn, Back Up: Whelen 600 Series LED.
1	STD	DOT Marker Lights: TecNiq LED, rubber grommet bezels; (7) S34-AC09-1 Amber- (5) on front of body as Marker lights, (2) side facing on rear extrusions as Turn Signals; (7) S34-RC90-1 Red- (5) on rear of Body as Marker lights, (2) side facing as Turn Signals.
	04-	Electrical, Power Distribution, Control Center & Interior Lighting
1	STD	Battery Switch, Automatic: TST CDR-400. Located in Electrical Cabinet.

2	STD	Batteries: OEM, 650 C.C.A. Locate: (1) Under hood, (1) In roll-out tray in Compartment #4/5
1	STD	Front Console/ Switch Panel: CNC cut, formed and powder coated aluminum body attached to cab floor. Switch panel: Engraved black plastic with (12) LED lighted switches for Emergency Master, Primary/Secondary Modes, Light Bar, Siren/Horn, Left, Rear and Right Floods, Back-Up Alarm, Module Disconnect. Siren mounted in engraved panel below switches.
2	STD	Antenna, Radio Coax Cable terminated behind driver's seat w/Power & Ground for each
1	STD	1 Camera System: RVS RVS-770-09 130 degree backup camera with infra-red illuminators and GM adapter harness. NOTE: For GM3500/4500 with OEM back up prewire and monitor system. Locate: Camera mounted off lower RH corner of center rear Amber light.
10	STD	Dome Lights: LED w/chrome flange; 2-banks of five (5) 18-diodes w/chrome flange MX80EHZA , switched separately with Hi/Lo functions.
1	STD	Action Area Light: Whelen PSC0ADCR, 12 VDC LED Strip light, 6 diodes and On/Off switch on rear control panel
1	STD	USB Port: Vanner VSS-USB dual port 2Amp mounted on A/A wall
1	STD	Shoreline: 125 VAC, 20-Amp, 60 Hz, straight blade inlet w/hinged, weatherproof cover, located above Compartment #2 SS
1	STD	Timer: 5-minute check-out, wired to CS High mode dome lights
1	STD	Inverter: Pre-Wire w/switch on rear panel. Pre-wire located in lower walk-thru cabinet
1	STD	Battery Conditioner, Power Source, 45-Amp- Lower WT cabinet
1	STD	Breaker Box: 125 VAC w/20-Amp Breaker located behind the driver's seat base. GFI receptacle located on the Action Area wall.
3	STD	12 VDC Outlets: (1) in Action Area, (1) in ALS Cabinet, (1) in 2nd Action Area on 166" mod
3	STD	125 VAC Outlets: Duplex, located 1-in Action Area, 1- in ALS, 1- 2nd Action Area on 166" mod
1	STD	Rear Switch Panel: Engraved black plastic panel with (14) LED lighted switch positions for Dome Lights (2), Vacuum (1), Vent (1), A.A. Light (1), Inverter (1), <u>Spare switches and digital clock w/Mode Buttons. MX01517.</u>
1	STD	Electrical Cabinet: Located over walk-thru w/latching, recessed, vented door
	05-	Warning Lights & Sirens
1	STD	Lights: Warning, Whelen LED EMERGENCY Lighting Package- Ford, Chevy <u>Type I and Type III- Models ONLY.</u> NOTE: Does not include LED Scene Lights.
		All LED lights shall have CLEAR Lenses. All emergency and scene lighting shall have chrome flanges in standard locations.
		Front of Body: Add (7) Whelen 900 Series Suprer-LEDs- Specify pattern by LED Color (Red or White: _____ Outer (2) lights and (1) Center light flash on K-Spec flasher. Inner (4) flash independently on Light Bar switch on front console.

		Sides of Body: (4) Whelen 900 Series Red Super-LEDs: (2) each side in upper corners
		Rear of Body: (4) Whelen 900 Series Red Super-LEDs: (2) in upper outboard corners, (2) Mid-Body wired as Warning/Brake at the window level; (1) Whelen 600 Series Amber Super-LED in the center position over the rear doors.
		Brake, Turn & Back-Up Lights: Whelen 600 Series LEDs
		Lights, Warning, Intersection Lights: (2) Whelen 700 Series Red Series Super-LEDs on front fenders.
2	STD	Lights, Warning, Grille: LINZ6R Red LED w/clear lenses & chrome flanges on center grille bar
4	STD	Lights: Scene, Whelen 900 Series Halogen with flange included - (2) Each Side of Module
2	STD	Lights: Load, Whelen 900 Series Halogen with flange included - (2) over rear entry doors
1	STD	Flasher- For Warning Light System, Vanner 9860GCPE
2	STD	Siren Speakers: dual 100 Watt drivers mounted through the front bumper
1	STD	Siren- Whelen 295SLSA1, 200 Watt
	06-	Oxygen, Vacuum & Miscellaneous Items
3	STD	Oxygen Outlets: Quick-connect style, 2-in Action Area, 1-over Squad Bench
1	STD	Suction Aspirator System: Rico disposable container mounted in Action Area w/gauge and quick-connect; SSCOR vacuum pump mounted in lower walk-thru cabinet
1	STD	Oxygen Cylinder Retention: For "M" cylinder, black steel w/3-spring buckle straps and top collar, located in Compartment #1
1	STD	O2 Regulator, Amvex, 50psi, pre-set
	07-	AC / Heat
1	STD	HVAC System: High capacity ProAir, brushless free blow combination Heat-AC system with digital thermostat control on the action area wall. HVAC unit mounted in front bulkhead above the tech seat.
	08-	Cabinets, Hardware & Miscellaneous Items
1	STD	Main Streetside Wall Cabinets: Specify desired configuration-
0	OPT	Full Wall of Cabinets
0	OPT	Streetside Cabinet Configuration shall include a CPR Seat with Pro-4 seat belt system. The seat belt system shall include a custom contoured seat back, a single click Pro-4 seat belt, custom pads on the upper straps for shoulder comfort and a heat embossed Medix LOGO at the heat area. There shall be a 2nd Action Area, which includes (1) 125VAC and (1) 12VDC outlet, located aft of the CPR seating area.
		Main Wall Cabinets will have (1) adjustable shelf in each and sliding polycarbonate doors with full height extruded handles. See Prints for Configuration.
1	STD	Action Area Overhead Cabinet: Single cabinet full-height/full-depth of Action Area with sliding polycarbonate doors and full height extruded handles.

1	STD	Action Area and Switch Panel: Laminated, sealed countertop and vertical panel with Suction system collection canister, Vacuum gauge, (2) Oxygen outlets, (1) USB, (1) 12VDC Outlet, (1) 125VAC Outlet and digital Thermostat. Switch panel MX01517 includes (10) switch positions and digital clock w/Mode Buttons.
1	STD	Inside/Outside access to Compartment #3: With dual 1/2" Acrylic hinged doors w/non-locking Eberhard two point pinch latches.
2	STD	Bulkhead Wall Cabinets: HVAC cabinet above Tech Seat; Electrical Cabinet located above walk-thru w/hinged, latching, vented door
1	STD	Bulkhead Cabinets: Upper cabinet- general storage w/hinged, latching door; Lower cabinet general storage w/hinged, latching, vented door and location for inverter and vacuum pump on floor.
1	STD	Cabinet Above ALS: Open storage w/dual 1/2" Acrylic doors w/non-locking Eberhard two point pinch latches each door, (1) adjustable shelf.
1	STD	ALS Cabinet: Lower section- Locking LifeDefender latch with storage for 747 box, Middle & Upper Section- general storage with non-locking doors and 1-adjustable shelf.
1	STD	Squad Bench:
	1	Full length hinged lid w/TriMark latch for access to interior storage.
	2	Full length upholstered seat cushion except over Sharps/Waste Area; formed upholstered back rest cushions and head pad for each seated position.
	3	2) EVS Pro-4 seat belt system seating positions. The seat belt positions shall include a custom contoured seat back, a single click Pro-4 seat belt, custom pads on the upper straps for shoulder comfort, a custom retractor for securing a secondary patient and a heat embossed Medix LOGO at the heat area.
1	STD	Sharps/Waste: Drop-in style with aluminum, powder coated red, hinged lid and standard containers, located at head of squad bench.
1	STD	Cabinet, Squad Bench Overhead: w/ (2) flip-up 1/2" Acrylic doors with (2) Eberhard two point squeeze latches and Southco torque hinges.
1	STD	Cabinet, Rear Overhead: Cabinet over rear door opening w/polycarbonate sliding doors w/full height extruded handles
1	STD	Technician's Seat: An EVS Rear facing custom contoured, automotive style, high back seat with the Pro-4 seat belt system mounted on an EVS structural steel base. The seat belt system shall include a custom automotive style seat, a single click Pro-4 seat belt, custom pads on the upper straps for shoulder comfort and a heat embossed Medix LOGO at the head area.
1	STD	Assist Rail, overhead off-center toward Streetside of unit.
3	STD	Grab handle- stainless steel, mounted on each rear entry and curbside entry door
9	STD	Reflective Striping, Door Open Protection: .50" Red reflective striping around interior door pan of all body doors.
	09-	Cots & Miscellaneous Items
0	STD	Cot Mount: NOTE - Must supply cot mount requirements with order.

	10-	Paint & Lettering
1	STD	Paint: Body all OEM White
0	1000100	Roof Star ONLY, INSTALLED
		SHIP LOOSE
2	STD	5 Lb. Fire Extinguisher- Ship Loose is Standard
TOTAL ORDER		

I have reviewed this Order and find it to be acceptable and ready to build.

_____ **Date:** _____
 Dealer Signature

I have reviewed this Order and find it to be acceptable and ready to build with the addition of the attached, approved changes.

_____ **Date:** _____
 Dealer Signature

Due to on-going product improvements and the changing requirements of the ambulance industry, MEDIX Specialty Vehicles, Inc. reserves the right to change product specifications and related products without prior notice and without any obligation to change prior products or parts. ALL PATENTS RIGHTS RESERVED.