

## Dependable protection with a reliable grip

- Prevents rips and tears due to thicker fingertips than most standard latex gloves
- Delivers a secure and dependable grip for rugged work settings especially in oily environments
- Allows easy donning and a cooler, drier and more comfortable fit
- Provides excellent protection for automotive industry applications



### Industries

- Automotive
- Dental
- Electronics
- General Exam
- Healthcare
- Laboratory
- Life Sciences (Pharmaceutical, Biopharmaceutical & Medical Devices)

### Applications

- Analytical testing/measurements
- Assembly and inspection of oil-coated pieces
- Cleaning
- Crime scene evaluation
- Dental
- Filtration Processes
- Food and dairy processing
- Handling small parts
- Healthcare
- Janitorial and maintenance work
- Paint and spray shops
- Picking and assembling wet or dry parts
- Protection from blood and other bodily fluids
- Re-fueling
- Warehousing

**TECHNICAL DATA SHEET:**

**PRODUCT INFORMATION:**

	Diamond Grip <sup>™</sup>
<b>Material</b>	Latex
<b>Color</b>	Natural
<b>Glove Design</b>	Ambidextrous, Powder-Free, Double Chlorinated, Textured Fingertips
<b>Cuff</b>	Beaded Cuff
<b>Manufacturing/ QMS Audit Standards</b>	ISO 13485
<b>Regulatory/Standards Compliance</b>	ASTM D3578, US QSR/FDA 510(K) MEDICAL (EXAMINATION) GRADE, COMPLIANT WITH U.S. FOOD CONTACT REGULATIONS
<b>Packaging</b>	100 Pack: 100 gloves per dispenser, 10 dispensers per shipper carton, 1000 gloves per shipper carton. 10 Pack: 10 gloves per pouch, 50 pouches per shipping carton, 500 gloves per shipping carton.
<b>Storage</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country of Origin</b>	Malaysia
<b>User Needs Segment</b>	Robust Glove - Gloves that provide added strength, durability and chemical splash protection for longer wear times.

**PHYSICAL PROPERTIES:**

	TYPICAL VALUES					TESTING METHOD
	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	
Length (mm/in.)	245/9.6	245/9.6	245/9.6	245/9.6	245/9.6	ASTM D3767/EN 420
Average Palm Width (mm/in.)	76/2.99	83/3.26	95/3.74	107/4.21	117/4.60	
Freedom from Holes (Inspection level I)	1.5 AQL					ASTM D5151/EN 374-2
Palm Thickness Single Wall	(mm : 0.16) / (mil : 6.3)					ASTM D3767/EN 420
	BEFORE AGING		AFTER AGING			
Ultimate Tensile Strength	> 27 Mpa		> 23 Mpa		ASTM D 412-06a	
Elongation at Break (%)	> 750		> 600		ASTM D 412-06a	
Force at break (N)	16		6		EN 455-2	

**ORDERING INFORMATION:**

	SIZE	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL
Diamond Grip 100 glove dispenser	REORDER NO.	MF-300-XS	MF-300-S	MF-300-M	MF-300-L	MF-300-XL
Diamond Grip 10 pack pouch is only available in Large					MF-300-RP	

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application

Warning: This product contains natural rubber latex, which may cause allergic reactions in sensitive individuals.

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at 1-877-750-6110

Ansell  
111 Wood Avenue South  
Suite 210  
Iselin, NJ 08830  
USA

Ansell  
105 Lauder  
Cowansville, QC J2K 2K8  
Canada